# Cat® Extreme Application Grease

For high-load, high-speed applications

NLGI Grade 1, 2



# **Discover the Difference**

**Long Life**—High-quality calcium sulfonate complex formula with 5% molybdenum disulfide (moly) for long service life in Cat applications.

Moisture Resistance—Resists washout from fresh and salt water.

**Reduced Component Wear**—Resists softening and continues to protect parts under extreme loads and high-speeds.

**Corrosion Protection**—Resists oxidation and protects metal against rust. Will not corrode or damage steel, copper bearing alloys or conventional seal materials.





# **Cat® Extreme Application Grease**

## **Grease Selection Guide**

**Cat Extreme Application Grease 1** NLGI 1 (-20 to 140°C / -4 to 284°F)

Cat Extreme Application Grease - Desert NLGI 2 (+10° to 140°C / +50° to 284°F)


With 5% Moly

**Cat Prime Application Grease** NLGI 2 (-20 to 140°C / -4 to 284°F)

With 3% Moly

**Cat Ball Bearing Grease** NLGI 2 (-20° to 160°C / -4° to 320°F)

Without Molv



**Cat Extreme Application Grease - Arctic NLGIO** (-50° to 130°C / -58° to 266°F) With 5% Molv

**Low Temp** 

Med Load & **Med Speed** 

Without Molv Low Load & **Low Speed** 

**Cat Utility Grease** 

NLGI 2

(-20 to 140°C / -4 to 284°F)

Low Load & **High Speed** 

* All temperatures are Operating T	emperatures

Typical Characteristics			
NLGI	1	2	
Color	Gray Black		
Molybdenum Disulfide, %	5	5	
Operating Temperature Range, °C	-20 to +140	-15 to +140	
Operating Temperature Range, °F	-4 to +284	+5 to +284	
Base Oil Type	Mineral		
ASTM D445 Base Oil Viscosity 40°C, mm²/s	150		
Thickener Type	Calcium Sulfonate		
ASTM D2265 Dropping point, °C	> 260	> 260	
ASTM D2266 4 Ball wear, scar diameter, mm	.39	.39	
ASTM D2596 4 Ball weld load, kg	800	800	
ASTM D1743 Rust prevention	Pass	Pass	
ASTM D4048 Copper corrosion	1A	1A	
ASTM D1264 Water wash-out, 79°C, mass %	0.6	0.6	

#### **Recommended Use**

Cat Extreme Application Greases are formulated for grease fittings and lubrication points in high-load, high-speed applications with operating temperatures ranging from -20°C to +140°C  $(-4^{\circ}F$  to  $+284^{\circ}F)$  for NLGI 1 and -15°C to 140°C (+5°F to +284°F) for NLGI 2.

### **Health and Safety**

For information on proper use for health, safety and environment, please refer to the Material Safety Data Sheet (MSDS). using this product. Always observe good hygiene measures. For a copy of the MSDS, contact us or visit the web at www.catmsds.com.

The values shown are typical values and should not be used as quality control parameters to either accept or reject product. Specifications are subject to change without notice.

## CAT DEALERS DEFINE WORLD-**CLASS PRODUCT SUPPORT.**

We offer you the right parts and service solutions, when and where you need them.

The Cat Dealer network of highly trained experts keeps your fleet up and running to maximize your equipment investment.

# **BUILT FOR IT**





